

# PORTABLE CARBON DIOXIDE GAS FIRE EXTINGUISHERS

## I General:

It is a new type of high effective and completely clean extinguisher, Inside there is high purity carbon dioxide gas. These extinguishers are often use on extinguishing the initial fire caused by flammable gas, liquid, and the optimum choice for protecting electrical equipment.



## III operation

Pull safe pin, then grasp horn, aim at fire, squeeze handle and sweep side to side (horn must in fire's oblique-up side).

## II Main Data

Model	At 20°C ± 5°C			Class Rating	Operating Temperature
	Capacity (kg)	Effective Bulk Range of Discharge (m)	Effective Discharge Time (s)		
MT2	2 <sup>0</sup> -0.1	≥ 1.5	≥ 8	2B	-10°C - +55°C
MT3	3 <sup>0</sup> -0.15	≥ 1.5	≥ 8	3B	
MT5	5 <sup>0</sup> -0.25	≥ 2	≥ 8	4B	
MT7	7 <sup>0</sup> -0.35	≥ 2	≥ 8	5B	

## IV Maintenance

1. Please don't place up side down and strike this extinguisher.
2. Keep away from strong sunlight and corrosive material.
3. Stored at clean and dry place with -10°C ~ +55°C notice protecting damp and don't near heat source.
4. Information for user : please assemble elbow and horn and screw to valve.
5. Check these extinguishers frequent, it must be recharge once operation or when leakage of the fire extinguishing agents exceed 50g.
6. It should be test by 22.5Mpa-hydrostatics pressure every 5 years. All maintenance should be performed by special maintenance place.